



EDUCATION
PROJECTOR

D857WT



The Short-Throw Performer

The Vivitek D857WT combines the best in performance, form factor, versatility and value. The D857WT offers ease-of-use in its operation. The Vivitek D857WT digital projectors also feature multiple connectivity options, DLP® and BrilliantColor™ technologies and up to 6000 hours of lamp-life.

Features

- Native WXGA resolution and able to display up to UXGA (1600 x 1200)
- 3000 ANSI Lumens of brightness with a 3000:1 contrast
- 3D-Ready via DLP® Link™
- High-efficiency lamps that last up to 6000 hours (in economy mode)
- Sealed optical engine
- Top-Loading for easy lamp replacement
- VGA-output for display on a secondary monitor
- Keypad lock prevents accidental system adjustments
- Enhanced color and display adjustments
- Network-ready for integration and system administration via RJ45

Specifications	
Brightness	3000 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	3000:1 (Full On/Off)
Lamp Life and Type	6000/4000 Hours (Standard/Boost Mode), 220W
Lamp Part #	5811116713-S
Display Type	Single 0.65" DLP® Technology by Texas Instruments
Throw Ratio	0.52:1(Distance/Width)
Image Size (Diagonal)	43" - 430"
Projection Distance	0.5 - 5.0 m
Projection Lens	F = 2.87, f = 7.36 mm
Zoom Ratio	Fixed Lens
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible
Offset	123%
Keystone Correction	Auto Keystone, ±15° Vertical
Color Spectrum	16.7 Million
Horizontal Scan Rate	50/60Hz
Vertical Scan Rate	43 to 85 Hz
Speaker	10 Watt
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.3, DVI-I, VGA-In, VGA-Out, Composite Video, Mini-Jack Audio-In, Mini-Jack Audio-Out, Microphone, RCA Stereo-In, RJ45, RS-232c, USB (Service)
Security	Kensington® Lock Port
Weight	2.7 kg
Dimensions (W x H x D)	306 x 104 x 206 mm
Noise Level	36dB/33dB (Normal / Eco Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Standard Mode), 280W (Boost Mode), <1W (Standby Mode)
Warranty	3-Year Warranty, 1-Year or 1,000h on Lamp
Education Warranty	5-Year Warranty, 3-Year (or max. lamp lifetime)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	814964 335357

