

MFC-9320CW

TN230CMYK/ DR230CL

**High Speed Wireless Colour All-in-One Printer with Fax**



**Copy**

Convenient, compact and unbelievably quick both in colour and mono – this is the perfect machine if you're pushed for space. It produces professional looking colour documents easily and efficiently and can be shared by the whole office without the hassle of extra wires everywhere – bliss!

**Catalogue Spec**

- Space saving, reliable and fully featured colour multifunction printer makes this idea for small offices
- Fast mono and colour printout speed of 16ppm
- Easy and secure wireless connection gives you the freedom to work anywhere
- Wired network ready
- Increase efficiency with the direct print USB Host port
- Hi Speed Faxing
- High quality network colour scanning
- Time saving 35 sheet automatic document feeder
- large 250 sheet paper meaning less time spent filling the tray
- Built-in LCD screen allows PIN protected secure printing
- Energy Star certified meaning low energy usage
- 12 months warranty and lifetime telephone/ web support

## Detailed Spec

### General

|                          |  |
|--------------------------|--|
| Engine                   | Electrophotographic LED (single-pass)  |
| Processor                | 64bit RISC VR5500 300MHz   |
| Interface                | Hi-Speed USB 2.0 / Built in 10/100 Base-TX Network   |
| Security                 | Wireless LAN IEEE802.11b/g (Infrastructure Mode/Adhoc mode)  |
| Network Protocols        | WEP 64/128bit, WPA-PSK (TKIP/AES), WPA2-PSK (TKIP&AES), LEAP, EAP-FAST   |
| IPv4                     | TCP/IP (IPv4 and IPv6)<br>ARP, RARP, BOOTP, DHCP, APIPA(Auto IP) WINS, NetBIOS name resolution, DNS Resolver, mDNS, LLMNR<br>responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPSServer, TFTP client and server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SNMPv1/v2c/v3, ICMP, LLTD responder, WebServicesPrint, CIFS Client, SSL/TLS |
| IPv6 (Off by default)    | NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, APOP, POP before SMTP, SMTP-AUTH, SNMPv1/v2c/v3, ICMPv6, LLTD responder, WebServicesPrint, CIFS Client, SSL/TLS  |
| LCD Display Size         | 2 lines of 16 characters with Green Back-lit Display   |
| On-Screen Programming    | Step by step prompts are displayed within the LCD in order to facilitate programming machine options and settings  |
| Standard Memory Capacity | 64MB (RAM)   |
| Optional Memory          | Expandable up to 576MB using 144 pin DIMM  |
| Simultaneous Operation   | (Print/Fax), (Print/Copy), (Print/Scan)  |
| On / Off Switch          | Yes  |

### Colour Printer

|                             |   |
|-----------------------------|---|
| Speed                       | Up to 16ppm colour & mono                                 |
| Resolution                  | Up to 2,400x600dpi*** resolution [2,400dpi class]         |
| First Print Out Time        | Less than 16 seconds colour, 15 seconds mono              |
| Warm Up Time                | Less than 27 seconds from sleep, 37 seconds from power on |
| Paper Capacity** (Standard) | Up to 250 sheets can be stored in the paper tray          |
| Output Paper Capacity**     | Up to 100 sheets can be stored in the output paper tray   |

### Colour Copier

|                                       |  |
|---------------------------------------|--|
| Speed                                 | Up to 16cpm colour & mono  |
| First Copy Out Time (From Ready Mode) | Less than 24 seconds colour, 19 seconds mono                         |
| Resolution                            | Maximum 1,200 x 600 dpi  |
| Multi-Copying / Stack / Sort          | Makes up to 99 copies of each page / Stacks or Sorts                 |
| Enlargement / Reduction Ratio         | Reduce or Increase document sizes from 25% to 400% in 1% increments. |
| N in 1 Copying                        | Allows the user to compress 2 or 4 pages on to a single A4 sheet.    |

### Colour Scanner

|                           |   |
|---------------------------|---|
| Resolution (Optical)      | 1,200 x 2,400dpi  |
| Resolution (Interpolated) | 19,200 x 19,200dpi  |
| Colour Depth              | This model has a 48bit internal / 24bit external Colour Scanner |
| Grey Scale                | 256 shades of grey are available for copying or scanning        |
| TWAIN Scanner Compliance  | Windows® 2000 and OS X 10.3.9 or greater                        |
| WIA Scanner Compliance    | Windows Vista®, Windows® XP                                     |
| SANE Scanner Compliance   | Linux   |
| Scan Key                  | Enables user to scan a document to e-mail, Image, OCR, file.    |

### Colour Fax

|                            |   |
|----------------------------|---|
| Modem Speed                | 33, 6kbps   |
| Transmission Speed         | 2 seconds (Brother #Std resolution, JBIG)   |
| ITU-T group compatibility  | Super G3  |
| Data Compression           | MH / MR / MMR / JBIG / JPEG   |
| Backup for clock           | Up to 60hrs   |
| Memory Backup              | Up to 60hrs (only for standard memory)  |
| Memory Security            | Allows prevention of unauthorised access to the fax machine   |
| Automatic Redial           | Automatic redialling if the recipient fax is busy   |
| One-Touch Dials            | Auto dialling of a pre-stored number performed by the touch of one key, 16 locations (2 x 8)  |
| Speed Dials                | Auto dialling of pre-stored number by entry of a three digit number (300 locations)   |
| Group Dial                 | A combination of up to 20 One-Touch and telephone index numbers can be stored on a One-Touch key for broadcasting   |
| Telephone Index            | An electronic, alphabetical listing of stored One-Touch, Speed Dial and Group numbers   |
| Chain Dialling             | Allows the user to store parts for long dialling sequences in different One-Touch or Speed Dial locations   |
| Station ID                 | This is the stored information that appears on the top of faxed pages   |
| FAX / TEL Switch           | Automatic recognition of Fax and Telephone reception  |
| Distinctive Ring Detection | A service purchased from the Telephone Company that allows two or more telephone numbers to share a single fixed line, the function enables the machine to provide a different ring tune for each number. (Available only for UK and Denmark) |
| Speaker / Ring volume      | 3 Steps and off   |
| Grey Scale                 | 256 levels  |
| Contrast                   | This allows the user to change the contrast between Auto / light / dark   |
| Delayed Timer              | Up to 50  |

|                                  |  |
|----------------------------------|--|
| Polling                          | This feature enables a machine to request another machine to send information on demand  |
| Quick-Scan (Memory Transmission) | Reduce scanning times by scanning a fax into memory before sending. Approximately 2 seconds per page   |
| Out of Paper Reception           | Up to 500 pages (ITU-T Chart/JBIG/Standard Resolution)   |
| Broadcasting                     | Up to 600 pages (Brother #Chart/Standard Resolution/JBIG)  |
| Batch Transmission               | Send the same fax message to up to 366 separate locations (Groups, One-Touch, Speed-Dial numbers and up to 50 manually dialled numbers)                |
| Auto Reduction                   | Stores documents for the same location in the machines memory for transmission in a single call  |
| ECM (Error Correction Mode)      | When receiving a single page document between 297mm and 350mm long the fax machine will automatically reduce the message to fit onto a single A4 sheet |
| Dual Access                      | Where machines share the ECM feature, it will detect line errors during fax transmission and resend the page(s) of the document that had an error      |
| Fax Forwarding                   | Allows the user to dial a number, and begin scanning the fax into memory, even when the MFC is receiving, sending or printing a fax from memory.       |
| PC Fax Send & Receive            | Sends a fax received in memory to another pre-programmed fax number  |
| Remote Access                    | Sends & receives faxes direct from / to your PC. (Send only for Mac & Linux)   |
|                                  | Allows the user to remotely access their machine by using another touch tone phone   |

### **Printer Driver**

|            |  |
|------------|--|
| Windows®   | Printer Driver for Windows® 2000 Professional, XP Home Edition, XP Professional (32 & 64 bit editions), Windows Server® 2003/2008 (32 & 64 bit editions), Windows Vista® |
| Macintosh® | Macintosh Printer Driver for Mac OS X 10.3.9 or greater  |
| Linux      | Linux printer driver for CUPS printing system(x86 , x64 environment), Linux printer driver for LPD/LPRng printing system(x86 , x64 environment).                         |

### **Standard Print Language**

|                     |   |
|---------------------|---|
| Emulation           | PCL®6 & BR-Script 3 (PostScript®3 Language Emulation) |
| PCL® Resident Fonts | 66 scalable fonts, 12 bitmap fonts, 13 bar codes      |
| BR-Script 3         | 66 Fonts  |

### **Secure Print**

Print jobs can be password protected and printed only when the individual password is entered

### **Printer Driver Functions**

|                      |   |
|----------------------|---|
| N-up Printing        | Reduce up to 2, 4, 9, 16 or 25 A4 pages into just one A4 page   |
| Poster Printing †    | Enlarge 1 A4 page into a poster using 4, 9, 16 or 25 A4 pages   |
| Watermark Printing † | Watermark your documents with predefined text or with your own user-defined messages                  |
| Booklet Printing †   | Print documents in A5 Booklet format using manual duplex  |
| Secure Print †       | Protect your print jobs with a pin number, enter the pin number at the machine to print the documents |
| Reprint †            | Quickly reprint the last print job sent to the machine by pressing the Reprint key                    |
| Colour Restrict †    | Colour restriction tool from printer driver   |

### **Network Management Utilities**

|               |                              |
|---------------|------------------------------|
| BRAdmin Light | For setup and LAN management |
|---------------|------------------------------|

### **Web Downloadable Network Management Utilities - <http://solutions.brother.com>**

|                      |   |
|----------------------|---|
| BRAdmin Professional | By web download for LAN management                    |
| Web BRAdmin          | By web download for LAN/WAN management                |
| Web Based Management | A printer and print server management through the web |

### **USB Direct Interface**

|                      |   |
|----------------------|---|
| Pictbridge           | Print directly from a PictBridge enabled Digital Camera   |
| USB Direct Interface | Print & Scan directly from/to USB Flash Memory Drive  |
| File Formats         | PDF version1.7, JPEG, Exif + JPEG, PRN(created by MFC-9320CW series printer driver), TIFF(MH/ scanned by Brother model) |

### **Paper Handling**

|                |   |
|----------------|---|
| Paper Input**  | Standard Tray: 250 sheets                       |
|                | Manual Feed Tray: 1 sheet                       |
|                | ADF (Automatic Document Feeder) Up to 35 sheets |
|                | Optional Lower Tray: N/A                        |
| Paper Output** | Face Down: 150 sheets                           |
|                | Face Up: 1 sheet                                |
| Manual Duplex  | Yes   |

### **Media Specifications**

|               |   |
|---------------|---|
| Media Types   | Standard Tray: Plain paper, Thin Paper, Recycled Paper  |
|               | Manual Feed Slot: Plain paper, Thin Paper, Thick Paper, Recycled Paper, Bond, Label, Envelope |
| Media Weights | Standard Tray: 60 – 105g/m²   |
|               | Manual Feed Slot: 60 – 163g/m²  |
| Media Sizes   | Standard Tray: A4, Letter, ISOB5, A5, A5(Long Edge), ISOB6, A6, Executive, Legal, Folio       |
|               | Manual Feed Slot: Width (76.2 – 220mm) x Length (116.0 x 406.4)                               |

### **List / Report**

|                    |  |
|--------------------|--|
| Help List          | By using the reports option, a list of basic operational steps and functions can be printed  |
| System Set-up List | A printed report that shows the current setting of your machine.   |
| Order form         | An accessories order form can be printed for you to send to your Brother dealer by using the reports option and selecting Order Form |

### **Page Counters - Available to view in LCD or print**

|                   |  |
|-------------------|--|
| Total Print Pages | Informs the user of the total number of all pages produced from this machine     |
| Copy Pages        | Informs the user of the total number of copies made on this machine in pages     |
| PC Print Pages    | Informs the user of the total number of PC prints from this machine              |
| Report Pages      | Informs the user of the total number of reports printed on this machine in pages |

### **List / Report**

|                                       |   |
|---------------------------------------|---|
| Journal Report                        | Lists information about the last 200 incoming and outgoing faxes  |
| TX (Transmission) Verification Report | Reports transmission details after each fax is sent   |
| Electronic Cover-page                 | Generates a cover page at the recipient's machine   |
| Help List                             | By using the reports option, a list of basic operational steps and functions can be printed   |
| Quick Dial list                       | Lists names and numbers stored in One-Touch and Speed Dial memory, in numerical or alphabetical order                                 |
| Caller ID List                        | A printed report that shows a list of caller ID's the machine has received.   |
| System Set-up List                    | A printed report that shows the current setting of your machine.  |
| Order form                            | An accessories order form can be printed for you to send to your Brother dealer by using the reports option and selecting Order Form. |

### **Page Counters - Available to view in LCD or print**

|                         |   |
|-------------------------|---|
| Total Print Pages       | Informs the user of the total number of all pages produced from this machine                        |
| Copy Pages              | Informs the user of the total number of copies made on this machine in pages                        |
| PC Print Pages          | Informs the user of the total number of PC prints from this machine                                 |
| Fax RX and Report Pages | Informs the user of the total number of faxes received and reports printed on this machine in pages |

### **Supplies**

|                       |  |
|-----------------------|--|
| Mono Toner (K)        | TN-230BK: Standard yield of 2,200*   |
| Colour Toners (C,M,Y) | TN-230C: Standard yield of 1,400*  |
|                       | TN-230M: Standard yield of 1,400*  |
|                       | TN-230Y: Standard yield of 1,400*  |
| Drums                 | DR-230CL: 15,000 A4 pages (one page per job) (4 separate drums 1 each for CMYK)<br>DR-230CL-BK: 15,000 A4 pages (one page per job) (1 separate drum for BK)<br>DR-230CL-CMY: 15,000 A4 pages (one page per job) (1 separate drum for either CMY) |
| Belt Unit             | BU-200CL: Up to 50,000 A4 (one page per job)   |
| Waste Toner Box       | WT-200CL: 50,000 Pages @ 5% coverage for CMYK each   |

The frequency of replacement of consumables will vary depending on the complexity of the prints, the percentage of coverage, paper size, page per job, and the type of media.

### **Dimensions & Weights**

|                                  |  |
|----------------------------------|--|
| With carton & consumables        | 743 (W) x 592 (D) x 575 (H) mm, 29Kg   |
| Without carton, with consumables | 428 (W) x 491 (D) x 401 (H) mm, 22.9Kg |

### **Power Consumption**

|         |                     |
|---------|---------------------|
| Copying | Average 480w at 25c |
| Ready   | Average 75w at 25c  |
| Sleep   | Average 12w at 25c  |

### **Sound Pressure Level**

|         |                 |
|---------|-----------------|
| Copying | Less than 53 dB |
| Ready   | Less than 30 dB |

### **Sound Power Level**

|         |                  |
|---------|------------------|
| Copying | Less than 6.5 BA |
| Ready   | Less than 4.8 BA |

### **Ecology**

|              |   |
|--------------|---|
| Power Saving | This enables the machine to consume less energy when not in use.                      |
| Toner Saving | This reduces the toner usage and helps to reduce the total cost of printer ownership. |
| Energy Star  | Certified to the world-wide eco label for power consumption.                          |

### **Duty Cycles**

|             |  |
|-------------|--|
| Recommended | 300 – 1,500 pages monthly print volume |
| Maximum     | 25,000 pages monthly print volume      |

### **Optional Accessories**

Memory expandable up to 576MB total using standard 144pin DIMM cards (Not available from Brother)

\* Approx. yield is declared in accordance with ISO/IEC19798.

\*\* Calculated with 80g/m<sup>2</sup> paper

† Windows<sup>®</sup> only